

Broadband SOHO Gateway Router w/ 4-port Switch Part No. eG4TR

The eGig eG4TR is the ideal all-in-one networking solution for any home and small business user. The router features a fully functional built in firewall designed to protect against hacker attacks, and other Internet invasions. Whether it's email communication, downloading software, or just surfing the Internet, the eG4TR provides the secure connection to the Internet you need.

Product Features

Provides natural firewall and secure gateway for LAN users

Multiple users share a single ISP account

Allows Internet connectivity for up to 253 PCs

Supports DSL or Cable connection up to 8Mbps

Supports PPPoE DSL connection

Supports TCP/IP protocols

Supports Network Address Translation (NAT)

Dial-on-Demand & Auto-Disconnection (PPPoE DSL)

Supports Windows 95/98/NT/2000/ME/XP, Mac OS, UNIX



Simple configuration using either a terminal program, a Windows based setup, or Web browser

Easy LAN installation with 10/100Mbps Switched connections (automatically detected)

Built-in DHCP service automatically assigns network address, and identifies Domain Name Server and Default Gateway for each LAN user.

Specifications

Router (WAN) **Broadband Connection** High-speed DSL or Cable connection **DSL** Connection Always-On, PPPoE, DANA WAN Interface Speed 10/100Mbps Network Interface RJ45 (TP) Protocol Support TCP/IP DHCP (client) Support **PPPoE DSL Connection** Virtual Private Network (VPN) (PPTP pass-through)

Router (LAN)

Network Operating System Windows 95/9, Windows 2000/NT/ME/XT Mac OS, Unix Protocol TCP/IP. NAT Built-in DHCP Server Virtual Server User-definable Static Routing Table Internet Access Control (Packet Filtering) Firewall

Fast Ethernet Switch

Standards Compliance IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX Number of Ports 4 Switched 10/100Mbps Auto-negotiation Access Method Ethernet CSMA/CD Switching Method Store and Forward MAC Address Table 1K **Buffer Memory** 128K Bytes (shared) Filter and Forwarding Rate Line-speed Internal Bandwidth 500Mbps



Back view of eG4TR

General

Dimensions: Power Supply: Power Consumption: Operating Temperature: Storage Temperature: Humidity: Certification:

103 x 82 x 26 mm 5V DC 2.4A 12 Watts Max. 0 to 40 degree C -20 to 65 degree C 5% to 95% (non-condensing) FCC A, CE

Specifications in this document are subject to change without notice.